

Corrosive Gas Hoses

Ratermann Manufacturing, Inc. offers an All-Welded Monel Style hose – a zero permeation product!



INDEX

Corrosive Gas Hoses

- Corrosive Gas Hoses
4,250 PSIG **5C-2**

CORROSIVE GAS APPLICATIONS

PIGTAILS FOR CORROSIVE GAS APPLICATIONS 4,250 PSI



Hoses for Following Gas

Corrosive Gas Application up to Working Pressure of 4,250 PSI – Monel® Pigtails

1/4 inch I.D. Monel® corrugated inner core, stainless steel double braided, Monel® end fittings. Zero permeation, all welded construction ideal for corrosive gas applications.

Stamped with 4,250 PSIG MAWP, and month/year of manufacturer.



Female to Female

Standard Hose

Hose Length	Part #
24"	FPS-C24F14
36"	FPS-C36F14
48"	FPS-C48F14

With Armor Casing Anti-Kink, Anti-Whip

Hose Length	Part #
24"	FPS-A-C24F14
36"	FPS-A-C36F14
48"	FPS-A-C48F14

Male to Female

Standard Hose

Hose Length	Part #
24"	FPS-C24F14M14
36"	FPS-C36F14M14
48"	FPS-C48F14M14

With Armor Casing Anti-Kink, Anti-Whip

Hose Length	Part #
24"	FPS-A-C24F14M14
36"	FPS-A-C36F14M14
48"	FPS-A-C48F14M14

Male to Male

Standard Hose

Hose Length	Part #
24"	FPS-C24M14
36"	FPS-C36M14
48"	FPS-C48M14

With Armor Casing Anti-Kink, Anti-Whip

Hose Length	Part #
24"	FPS-A-C24M14
36"	FPS-A-C36M14
48"	FPS-A-C48M14

CUSTOM LENGTH HOSES - MONEL INNER CORE

4,250 PSI

*Custom length hoses are not returnable for either credit or refund.

ORDER CUSTOM LENGTH HOSE

Monel
Hose

With or Without
Armor Casing

FPS-C

- Armor Standard
Pt # A
- Non-Armor
Standard Pt # N

Length Hose


Inches
Pt # _____ IN

All hoses are
cleaned for
Oxygen Service

INLET

Choose Your Hose End Pt #


- 1/4" NPT Male Pt # M14
- 1/4" NPT Female Pt # F14



OUTLET

Choose Your Hose End Pt #

- 1/4" NPT Male Pt # M14
- 1/4" NPT Female Pt # F14



FPS-

- C

IN -