

RATERMANN

MANUFACTURING, INC.

ALUMINUM CARBON DIOXIDE CYLINDERS

for Industrial Gas



Models available include

- 2.5 lbs.
- 5 lbs.
- 10 lbs.
- 15 lbs.

SPECIFICATIONS

PART NO.	SERVICE PRESSURE		CO ₂ MAX. CAP.		N ₂ CAPACITY		OUTSIDE DIAMETER		OVERALL LENGTH		EMPTY WEIGHT		MIN. INTERNAL VOLUME		MIN. WATER WEIGHT		THREAD SIZE
	PSI	BAR	LBS	KG	CU.FT	LITERS	IN.	MM	IN.	MM	LBS	KG.	CU.IN	LITERS	LBS	KG	
CYL-CO2-2.5	1800	124	2.5	1.13	7.2	204	4.38	111.2	10.4	264	3.3	1.5	102	1.7	3.68	1.67	.750-16 UNF-2B
CYL-CO2-5	1800	124	5.0	2.30	14.5	411	5.25	133.4	14.0	356	6.2	2.8	205	3.4	7.40	3.36	1.125-12 UNF-2B
CYL-CO2-10*	1800	124	10.0	4.50	28.9	818	6.89	175.0	16.4	417	12.9	5.9	408	6.7	14.73	6.68	1.125-12 UNF-2B
CYL-CO2-15*	1800	124	15.0	6.80	43.3	1226	6.89	175.0	22.8	579	16.8	7.6	612	10.0	22.09	10.02	1.125-12 UNF-2B

* 10 lb. and 20 lb. have the option of either a Carry Handle (add "-H") or Cap and Collar (add "-CC").

Clean, corrosion-resistant, lightweight cylinders are ideal for dispensing carbonated soft drinks, beers, lagers and other beverages.

Features

- Lightweight, high strength 6061-T6 aluminum alloy improves cylinder system portability while reducing the rigors of material handling.
- Corrosion-resistant interior and exterior
- Brushed exterior provides a durable, low-maintenance finish for years of dependable service.
- Optional carrying handle offers superior valve protection.

Manufactured to DOT and TC requirements

- U.S. Department of Transportation (DOT) 3AL
- Transport Canada (TC) 3ALM
- Every cylinder inspected and tested by DOT- and TC-authorized independent agency
- Cycle-tested in excess of 100,000 cycles at service pressure
- Minimum burst pressure tested to 2.5 times service pressure without failure